








END-TO-END | Scooter Specifications

																					
	QUEST®	GO GOe®	GO GO® ULTRA X	GO GO® ELITE TRAVELLER 2	GO GO® LX W/ CTS SUSPENSION	GO GO® ENDURANCE L®	ZERO TURN 8	BAJA™ BANDIT	ZERO TURN 10	PATHRIDER® ES10	PATHRIDER® 10	PATHRIDER® 10 DX	VICTORY® 10 LX W/ CTS SUSPENSION	MAXIMA	PATHRIDER® ENDURANCE	CELEBRITY MFP	PATHRIDER® 130 XL	PATHRIDER® 140 XL	OUTBACK®	SPORT RIDER	
RANGE PER CHARGE (MAX) ^{2, 8}	Up to 19.3 km	Up to 14.4 km	3W: Up to 11 km 4W: Up to 11.5 km	Up to 16.7 km	Up to 16.9 km	Up to 23 km	Up to 16 km	Up to 23.3 km	Up to 28.8 km	Up to 17.9 km	Up to 25 km ¹³	Up to 25 km with 40AH ¹³	Up to 26 km	3W: Up to 31.4 km 4W: Up to 31.4 km	Up to 54.7 km	Up to 43.5 km	Up to 25 km ¹³	Up to 35 km ¹³	Up to 35 km	Up to 35 km	
MAXIMUM WEIGHT CAPACITY	113.3 kg	120 kg	118 kg	136 kg	136 kg	147 kg	136 kg	181 kg	170 kg	158.7 kg	158.7 kg	158.7 kg	181.4 kg	226.8 kg	158.8 kg	159 kg	158.7 kg	181.4 kg	158.7 kg	181.4 kg	
TURNING RADIUS ³	82 cm	125 cm	3W: 83.8 cm 4W: 100.3 cm	94 cm	116.2 cm	122.5 cm	97.2 cm	134.7 cm	109 cm	132 cm	137 cm	133.3 cm	152 cm	3W: 124.5 cm 4W: 134.6 cm	176 cm	158 cm	170 cm	210 cm right 208 cm left	243 cm	158 cm	
MAXIMUM SLOPE DEGREE	6°	6°	6°	6°	6°	6°	6°	6°	6°	10°	6°	6°	6°	3W: 6° 4W: 7.5°	10°	10°	10°	10°	10°	10°	
MAXIMUM SPEED ²	Up to 6 km/h	Up to 6.4 km/h	Up to 6.4 km/h	Up to 6.8 km/h	Up to 7 km/h	Up to 6.7 km/h	Up to 6.4 km/h	Up to 10 km/h	Up to 10 km/h	Up to 8.85 km/h	Up to 8.4km/h	Up to 8.85 km/h	Up to 9 km/h	Up to 9.3 km/h	Up to 9.7 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h	
LENGTH & WIDTH ^{3, 10}	L: 92.7 cm W: 49.5 cm	L: 100 cm W: 49 cm	3W: L: 94 cm 3W W: 49.5 cm 4W: L: 100.3 cm 4W W: 49.5 cm	L: 103.6 cm W: 49.4 cm	L: 104 cm W: 52.1 cm	L: 107 cm W: 52 cm	L: 116 cm W: 50.8 cm	L: 126 cm W: 56 cm	L: 122 cm W: 61.6 cm	L: 115.6 cm W: 57.1 cm	L: 115 cm W: 56.5 cm	L: 119.4 cm W: 56.2 cm	L: 119.4 cm W: 56.5 cm	3W L: 120.7 cm 3W W: 68.6 cm 4W L: 120.7 cm 4W W: 68.6 cm	L: 146 cm W: 75.3 cm	L: 145 cm W: 70.7 cm	L: 136 cm W: 63.6 cm	L: 142.8 cm W: 69.2 cm	L: 156 cm W: 83 cm	L: 165 cm W: 78 cm	
SEAT TYPE WIDTH & DEPTH (STANDARD)	Compact, foldable, molded plastic seat ⁵ W: 41 cm (16") D: 33 cm (13")	Compact, foldable seat ⁵ W: 41.9 cm (16.5") D: 33 cm (13")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 43 cm (17") D: 43 cm (17")	Compact, foldable seat ⁵ W: 46.5 cm (18.3") D: 44 cm (17.3")	Deluxe, pillow-top, high-back seat W: 49.5 cm (19.5") D: 44.5 cm (17.5")	Compact, foldable seat ⁵ W: 46 cm (18") D: 43 cm (17")	Compact, foldable seat ⁵ W: 46 cm (18") D: 43 cm (17")	Pillow-top, high-back seat W: 44.2 cm (17.5") D: 43 cm (17")	Pillow-top, high-back seat W: 46 cm (18") D: 46 cm (18")	High-back seat W: 55.9 cm (22") D: 50.8 cm (20")	High-back seat W: 55.9 cm (22") D: 50.8 cm (20")	Deluxe, pillow-top, high-back seat W: 49.5 cm (19.5") D: 44.5 cm (17.5")	Deluxe, pillow-top, high-back seat W: 49.5 cm (19.5") D: 44.5 cm (17.5")	Deluxe, pillow-top, high-back seat W: 49.5 cm (19.5") D: 44.5 cm (17.5")	Deluxe, pillow-top, high-back seat W: 49.5 cm (19.5") D: 44.5 cm (17.5")	Captains high-back, adjustable seat W: 51 cm (20") D: 56 cm (22")
SEAT-TO-DECK HEIGHT RANGE ³	31 cm fixed	41.9 cm - 45.7 cm	40 cm - 43.8 cm	41.6 cm - 45.3 cm	41.3 cm - 43.8 cm	41.2 cm x 45 cm	40.6 cm - 45.6 cm	47.5 cm suspension seat post	47.5 cm - 52.5 cm	37 cm - 42 cm	37 cm - 42 cm	43.8 cm - 47.6 cm	46 cm - 49 cm	44 cm x 60 cm	45.5 cm x 53 cm	45.2 cm - 49.9 cm	47 cm suspension seat post	55.3 cm - 57 cm	50 cm - 53 cm	48 cm fixed	
SEAT-TO-GROUND HEIGHT RANGE ³	51 cm fixed	54.6 cm - 59.7 cm	55 cm - 60 cm	46.3 cm - 51.4 cm	52.7 cm - 56.5 cm	53.9 cm x 59 cm	53.3 cm - 60 cm	66 cm suspension seat post	58.4 cm - 63.5 cm	51.4 cm - 55.2 cm	52 cm - 55.8 cm	60 cm - 63.8 cm	60 cm - 64.8 cm	56.6 cm - 72.6 cm	55.6 cm - 63 cm	66.7 cm - 70.5 cm	56.7 cm suspension seat post	66.7 cm - 70.5 cm	76 cm - 80 cm	68 cm fixed	
GROUND CLEARANCE ^{3, 11}	5.8 cm at frame	5 cm at transaxle	6.3 cm at midframe 3.8 cm at motor	3.4 cm at transaxle	6.4 cm at frame 3.8 cm at motor	3.6 cm at motor	8.9 cm at frame 3.3 cm at motor	4 cm at motor skid plate	5 cm at motor	8.8 cm at frame	7.6 cm at frame	8.25 cm at frame	5.6 cm at motor	5.7 cm at motor	9.6 cm at transaxle	8.8 cm at motor	9 cm at transaxle	13.3 cm at midframe	14 cm at midframe	12.7 cm at shroud	
OVERALL WEIGHT (NOT INC. BATTERY) ^{3, 12}	23.5 kg	32.5 kg	3W: 34.5 kg 4W: 36.3 kg	37.6 kg	39.4 kg	42.4 kg	53.9 kg	72.3 kg	82 kg	59.4 kg	62.4 kg	84.8 kg	81.2 kg	3W: 86.4 kg 4W: 92 kg	100 kg	104.3 kg	99.8 kg	117.7 kg	124 kg	115 kg	
WEIGHT OF HEAVIEST PIECE ³	23.5 kg (does not disassemble)	31 kg (does not disassemble)	3W: 13.4 kg 4W: 15.4 kg (front sections)	15.8 kg (front section)	16.6 kg (front section)	18.48 kg (front section)	21.8 kg (rear section)	31.8 kg (front section)	34 kg (rear section)	25.8 kg (front section)	27.7 kg (rear section)	29.5 kg (front section)	35.2 kg (rear section)	3W: 61.7 kg 4W: 67.3 kg (does not disassemble)	34 kg (rear section)	94 kg (does not disassemble)	34 kg (rear section)	93 kg (does not disassemble)	99 kg (does not disassemble)	92.3 kg (does not disassemble)	
SUSPENSION	N/A	N/A	N/A	N/A	CTS Front & Rear	CTS Front & Rear	CTS Front & Rear	Front, Rear & Seat Post	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	
3W/4W OPTION	4W	4W	3W & 4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	3W & 4W	4W	4W	4W	4W	4W	4W	
FRONT TYRES	1.5" x 7" solid	2" x 7.2" solid	3W: 2" x 8" solid 4W: 2" x 7" solid	2" x 7" solid	2" x 7" solid	2" x 8" solid	2" x 7" solid	2.5" x 9" solid	9" x 2.75" solid	3.6" x 10.4" solid	3.6" x 10.4" solid	3.6" x 10.4" solid	3.5" x 10" pneumatic	3.6" x 10" solid	3.5" x 13" pneumatic	4" x 13" pneumatic	4" x 13" pneumatic	4" x 13" pneumatic	14.5" x 6" pneumatic	2.75" x 19" pneumatic	
REAR TYRES	1.9" x 7.8" solid	2" x 8" solid	2.5" x 8" solid	2.5" x 8" solid	2.5" x 8" solid	2.5" x 8" solid	2.5" x 9" solid	2.5" x 9" solid	10.75" x 6" solid	3.6" x 10.75" solid	3.6" x 10.75" solid	3.6" x 10.75" solid	3.5" x 10" pneumatic	3.6" x 10.75" solid	3.5" x 13" pneumatic	4" x 13" pneumatic	4" x 13" pneumatic	4" x 13" pneumatic	14.5" x 6" pneumatic	2.75" x 19" pneumatic	
BATTERY REQUIREMENTS ⁶	11.5 AH (Lithium Ion)	(2) 12AH	(2) 12AH	(2) 18AH	(2) 18AH	16AH (Lithium Ion)	(2) 22AH	20AH, 36V (Lithium Ion)	(2) 40AH	(2) 31AH	(2) 31AH or (2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 50AH	(2) 50AH (Lithium Ion)	(2) 70AH	(2) 55AH	(2) 70AH	(2) 100AH	(2) 70AH	
BATTERY CHARGER	Off-Board 2.5A (Lithium Ion)	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-board, 3.5A (Lithium Ion)	Off-Board, 3.5A	Off-Board, 4A (Lithium Ion)	Off-Board, 3.5A	Off-Board, 3A	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 5A	Off-board, 5A	Off-Board, 8A (Lithium Ion)	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	
BATTERY WEIGHT ⁹	2.3 kg	2.5 kg	4 kg ⁴	6 kg	6 kg ⁷	5.4 kg	6 kg ⁷	9.5 kg	14 kg	10.5 kg	10.5 kg or 14 kg	10.5 kg or 14 kg	14 kg	16.6 kg	10.8 kg	22 kg ⁹	16.8 kg	23.45 kg	27.9 kg	23.7 kg	
COLOUR OPTIONS	White	Matte Black	Red	Red, Black	Red, Blue ¹	Garnet Red, Euro Grey ¹	Fire Opal, Pearl White, Sapphire Blue	Sage, Tan	Candy Apple Red, Black	Red	Viper Blue	Viper Blue	Candy Apple Red	Garnet Red, Ocean Blue	Black, Orange	Red, Blue	Candy Apple Red, Mercury Silver	Candy Apple Red, Yellow, Silver	Stone Grey	Black	

1 All shroud panels included. **2** Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of (+ or -) 10%. **3** Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. **4** 12 AH battery pack weighs 8.8 kg (19.5 lbs.). **5** Durable solid plastic. **6** Deep cycle (AGM or gel cell type recommended) excluding Lithium-ion models. **7** 18 AH battery pack weighs 13.4 kg (29.5 lbs.). **8** Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. **9** Battery weight may vary based on manufacturer. **10** Width of base (not including seat). **11** Does not account for anti-tip clearance. **12** Includes standard seat weight. **13** Range tested with 31-36 AH Batteries. Standard larger battery size would increase range. **NOTE** The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

